

Technical specification



Project ref: Alfa Laval
 Line ref:
 Model: ACH18-10H-F
 Item Id: 3287160212
 No of units: 1

Page: 1(2)
 Date: 2019-07-12

		Hot side S1 -> S2	Cold Side S3 -> S4
Process data			
Capacity:	kW	3,5	
Fluid:		Water	R407C
Mass flow rate:	kg/h	600	73
Inlet temperature:	°C	15,0	0,2
Outlet temperature:	°C	10,0	10,0
Evaporating temperature (dew):			5,0
Evaporating pressure:	bara		5,5
Super heating:			5
Inlet quality:			0,2126
Total pressure drop calculated (allowed)	kPa	16,8 (80,00)	13,0 (300,00)
Connection velocity in/out:	m/s	0,83/0,83	0,98/4,62
Margin calculated (specified):	%	12(0)	

Heat exchanger specification			
Relative directions of fluids:		Countercurrent	
Number of plates:		10	
Channel volume:	dm ³	0,2	0,2
Number of circuits:		1	1
Design pressure at -160 °C	bar	45	45
Design pressure at 150 °C	bar	45	45
Design temperature (min/max):	°C	-160 / 150	
Pressure vessel code:		PED	
Material Channel plates / Sealing:		ALLOY 316 / Cu	
Connection S1 (Hot-In):		Soldering 18 mm	
Connection S2 (Hot-Out):		Soldering 18 mm	
Connection S3 (Cold-In):		Soldering 18 mm	
Connection S4 (Cold-Out):		Soldering 18 mm	
Unit dimensions (length x width x height):	mm	50 x 74 x 316	
Net weight, empty / operating:	kg	1,3 / 1,50	
Packed length x width x height:	mm	0 x 0 x 0	
Packed weight:	kg	1,3	

The performance of the equipment is conditioned by the process media and process parameters being consistent with the provided customer data. Data, specifications, and other kind of information of technological nature set out in this document and submitted by Alfa Laval to you (Proprietary Information) are intellectual proprietary rights of Alfa Laval. The Proprietary Information shall remain the exclusive property of Alfa Laval and shall only be used for the purpose of evaluating Alfa Laval's quotation. The Proprietary Information may not, without the written consent of Alfa Laval, be used or copied, reproduced, transmitted or communicated or disclosed in any other way to a third party.